



Combiflex PU Threaded Sockets Food

cast-on PU threaded connector for attaching fittings to Master-PUR Food hoses, approved for direct food contact EU 10/2011, following DIN ISO 228

Product Details

Construction / Material

- Specification of the connection solution: connection thread is designed according to DIN ISO 228
- Execution of the sprue / collar: made of a material with high impact strength, made of specified material
- Material of the sprue / collar: Polyurethane
- Specification of the sprue / collar: approved for direct food contact according to EU Directive 1935/2004, 10/2011 and its latest amending Directives, material complies with the food regulations of BfR XXXIX

Properties

- Chemical Properties: hydrolysis resistant, microbe-resistant
- Colour: white
- Other: easy to assemble

Operating Temperature

- Temperature Range: -40 - 90
- short-term maximum temperature: peaks to 125 °C

Delivery Information

- Delivery, type of production: various nominal widths are available ex production, individual nominal widths also ex stock

Application Areas

Customizing Options

Article Variants

Article number	DN of the hose mm	Connection thread (G) Zoll	Piece weight kg	Length mm
005397	50	2	0.15	83
005408	65	2.5	0.22	94
/	75	3	not specified	102
005588	100	4	0.51	124
001480	125	5	0.60	100
005462	150	6	0.90	109

Subject to technical changes and colour deviations

Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).

Individual consultation

We offer consultation by
phone:
+49 209 97077-112

Product requests via
masterflex.de/en

Address Headquarters

Masterflex SE
Willy-Brandt-Allee 300
45981 Gelsenkirchen

